

Architectural drawings for Pit Latrines, including Elevation, Section, and Floor Plan views.

ELEVATION 01 (Scale= 1:50)

ELEVATION 02 (Scale= 1:50)

ELEVATION 03 (Scale= 1:50)

ELEVATION 04 (Scale= 1:50)

300X200mm RING BEAM
Section through Ring beam

SECTION 01-01 (Scale= 1:50)

FLOOR PLAN LAYOUT (Scale= 1:50)

STRIP FOUNDATION SECTION (1:30)

Floor Slab and Ground beam layout (Scale= 1:50)

300X200mm GROUND BEAM
Section through Ring beam

ROOF SPECIFICATIONS

- 6°DEG Timber truss roofing with 28 Gauge box profile Iron Sheetting and Accessories .
- > 3"x2" Main Rafters
- > 3"x2" king post
- > 3"x2" Struct & ties
- > 4"x2" Wall plate
- > 3"x2" purlins
- All timber pre-treated.

FLOOR & FOUNDATION SPECIFICATIONS

- a. Floor finish on 150mm thick concrete floor slab to Str. Eng. specs.
- b. D10 bars Mesh
- c. Polythene DPM 1000 Gauge
- d. 300mm Compacted hardcore
- e. 600 x 200mm Foundation footing or as per Str. Eng detail
- f. Foundation depth to be determined on site but at least 1200mm deep

Rev. **Description** **Date** **Drawn by:** **Designed by:** **Checked/Approved by:** **CLIENT:** **Project:** **Title:**

A	FIRST ISSUE	MARCH, 2025	FKN	MoALD	i. MoALD	MINISTRY OF AGRICULTURE AND LIVESTOCK DEVELOPMENT	AUXILIARY STRUCTURES FOR THE PROPOSED WATER PANS AND EARTH DAMS	PIT LATRINES
---	-------------	-------------	-----	-------	----------	---	---	--------------

Contract no. **Scale:** AS INDICATED

Drq. no.

Architectural drawings for Pit Latrines, including Elevation 01, Elevation 02, Elevation 03, Elevation 04, Section 01-01, Section through Ring beam, Floor Plan Layout, and Section through Ground beam.

ELEVATION 01 (Scale= 1:50)

ELEVATION 02 (Scale= 1:50)

ELEVATION 03 (Scale= 1:50)

ELEVATION 04 (Scale= 1:50)

SECTION 01-01 (Scale= 1:50)

Section through Ring beam

Section through Ground beam

FLOOR PLAN LAYOUT (Scale= 1:50)

STRIP FOUNDATION SECTION (1:30)

Floor Slab and Ground beam layout (Scale= 1:50)

ROOF SPECIFICATIONS

- 6°DEG Timber truss roofing with 28 Gauge box profile Iron Sheetting and Accessories .
- > 3"x2" Main Rafters
- > 3"x2" king post
- > 3"x2" Struct & ties
- > 4"x2" Wall plate
- > 3"x2" purlins
- All timber pre-treated.

FLOOR & FOUNDATION SPECIFICATIONS

- a. Floor finish on 150mm thick concrete floor slab to Str. Eng. specs.
- b. D10 bars Mesh
- c. Polythene DPM 1000 Gauge
- d. 300mm Compacted hardcore
- e. 600 x 200mm Foundation footing or as per Str. Eng detail
- f. Foundation depth to be determined on site but at least 1200mm deep

Rev. **Description** **Date** **Drawn by:** **Designed by:** **Checked/Approved by:** **CLIENT:** **Project:** **Title:**

Rev.	Description	Date	Drawn by:	Designed by:	Checked/Approved by:	CLIENT:	Project:	Title:
A	FIRST ISSUE	MARCH, 2025	FKN	MoALD	i. MoALD	MINISTRY OF AGRICULTURE AND LIVESTOCK DEVELOPMENT	AUXILIARY STRUCTURES FOR THE PROPOSED WATER PANS AND EARTH DAMS	PIT LATRINES

Contract no.
 Drg. no.
 Scale: AS INDICATED